

GF-P Series Pharmacy Balances

The GF-P Series balances have met the rigorous standards set forth by the National Conference on Weights and Measures Handbook 44, for legal-for-trade use. The GF-P balances are ideal for pharmacy and retail applications or any situation that requires legal-for-trade precision balances.

- Ideal for Pill Counting & Compounding
- Meets Handbook 44 Requirements for a “Class A” Prescription Balance
- Legal-for-Trade Prescription Balance
- IP-54 splash proof operator keyboard protects against dust and spills, stainless steel weigh pan
- GLP/GMP/ISO compliance
- One-Second Response Time



*Shown with optional tall breeze break.

GF-P SERIES SPECIFICATIONS

Model	GF-200P	GF-300P
Weighing capacity	210g	310g
Minimum weighing value	0.001g	
Repeatability (Standard Deviation)	0.001g	
Other units of measure	Decimal ounce, Troy ounce, Pennyweight, Grain unit, Pound, Pound/Ounce	
Linearity	±0.002g	
Stabilization time (typical at FAST)	Approx. 1 second	
Sensitivity drift (10°C to 30°C/50°F-80°F)	±2ppm/°C (When automatic self calibration is not used)	
Operating temperature	5°C to 40°C (41°F to 104°F), 85%RH or less (No condensation)	
Sensing method	Super Hybrid Sensor (SHS)	
Display type	Vacuum Fluorescent Display (VFD)	
Display refresh rate	5 times/second or 10 times/second	
Counting mode	Minimum unit mass	0.001g
	Number of samples	10, 25, 50 or 100 pieces
Percent mode	Minimum 100% reference mass	0.100g
	Minimum 100% display	0.01%, 0.1%, 1% (Depends on reference mass stored)
Standard serial I/F	RS-232C Interface with Windows Communication Tools (WinCT: included as CD-ROM)	
Weighing pan	128 x 128mm (5.04 x 5.04 inch)	
Calibration	External Calibration	
External dimensions	210(W) x 317(D) x 86(H)mm (8.27 x 12.48 x 3.39 inch)	
AC adapter	Confirm that the adapter type is correct for the local voltage and power receptacle	
Power consumption	Approx. 11VA (supplied by AC adapter)	
Net weight	Approx. 3.8kg	

Specifications subject to change without notice.

Options

- **GX-02*** Uni-directional USB interface with cable
- **GX-04*** Comparator Output with a Buzzer/RS-232C/Current Loop Output
- **GX-06*** Analog Output/Current Loop Output
- **GX-10** Tall Breeze Break for GF-200P & GF-300P
- **GX-12** Animal weighing pan except GF-200P
- **GX-13** Density Determination Kit for GF-200P & GF-300P

* If selected, only one of option GX-02, GX-04 or GX-06 can be installed (factory installed option).

Accessories

- **AD-8121B** Dot Matrix Compact Printer
- **AD-8920A** Remote Display
- **AD-1682** Rechargeable Battery Unit (Maximum operating time: 8 hours)
- **KO:WW9-25** RS-232C Cable (25P-9P)
- **SW-128** Foot Switch
- **AX-073003691-S** Dust Cover for GF-200 & GF-300P