

Uni-7_{series}



Hang_{ing} scale

Self-service

Pole

Bench

Elevator
single printer

Elevator
twin printer

Bakery

Specifications

| | |
|--|---|
| Weighing capacity (Dual Range): | 0-15 x 0.005lb; 15-30 x 0.010lb |
| Weighing accuracy: | 1/3000 |
| Operator Display: | Color LCD, 7 inch with positive input response |
| Customer Display: | Color LCD, 7 in |
| Display Items: | Tare: Four-digits Unit price: Six-digits Weight: Five-digits Total Price: Six-digits |
| Preset Keys: | 1980: 20 x 99 pages |
| Memory Capacity: | 2MB expandable to 2GB |
| Communications: | Static TCP/IP 10/100 Base T Ethernet Wireless WEP/WPA/WPA2 |
| Interface: | USB port |
| Print Head: | Direct thermal 2.2in head (56mm) |
| Print Speed: | 4.7 in (120mm) per second |
| Label Size: | Width: 1.2 in - 2.5 in (30mm - 64mm) Length: 0.8 in - 7.9 in (20mm - 200mm) |
| Label Roll: | Inside diameter: 1.6in (40mm) min Outside diameter: 3.9in (100mm) max |
| Label Backing Paper: | Width: Up to 2.6 in (66mm) |
| Power Supply: | AC100V/120V, 50/60 Hz |
| Power Consumption: | Stand-by: 50W, In operation: 120W |
| Classification: | NTEP CC 07-099, UL listed |
| Warranty: | One-year limited warranty |

Options

- SLP-V, PLU management software

Uni-7

models available



Hanging



Pole



Bench



Self-serve



Elevated
with receipt label



Elevated
single printer



Labeler
printer only

Your Rice Lake Weighing Systems distributor is:

RICE LAKE
RETAIL SOLUTIONS

ISHIDA

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com/retail

An ISO 9001 Registered Company
© 2011 Rice Lake Weighing Systems 02/11
Specifications subject to change without notice.